

MT-66

# BRAKE CLEANER

## ■ DESCRIPTION

Brake Cleaner is a powerful cleaner/degreaser for brake and clutch parts. A non-chlorinated solvent blend, formulated to quickly and safely remove brake fluid, grease, oil and other contaminants from brake and clutch parts. Brake Cleaner helps brakes last longer and perform better.

---

## ■ KEY FEATURES

- **Powerful Cleaning Performance:** Effectively removes brake dust, oil, grease, dirt, and grime from brake components without leaving residue.
- **Fast-Drying Formula:** Dries quickly for faster maintenance turnaround—no rinsing required.
- **Safe on Most Surfaces:** Designed to be non-corrosive and safe for use on **brake rotors, calipers, pads, drums, and other metal surfaces** when used as directed.
- **Non-Chlorinated & Low Odor:** Safer alternative to harsh chemical cleaners; non-chlorinated formulation with reduced toxicity and environmental impact.
- **Moisture Displacement:** Helps eliminate moisture from metal surfaces, reducing the risk of corrosion and improving performance of electrical and moving parts.
- **Reduces Noise and Vibration:** Helps restore braking efficiency by removing contaminants that cause squeaking or uneven wear.

- **Versatile Use Across Automotive Systems:** Ideal for cleaning:
    - Brake components
    - Clutch assemblies
    - Engine parts
    - Gearboxes and transmissions
    - Chains and sprockets
    - Bearings and housings
    - Electrical contacts (when used with caution and fully dried)
  - **Safe for Workshop Use:** Formulated to meet industry safety standards with low VOC emissions and minimal health risk when used properly.
  - **Improves Equipment Longevity:** Regular use helps maintain mechanical efficiency and extends the lifespan of automotive components.
-

## ■ TECHNICAL DATA

Appearance: Colorless Liquid

Specific Gravity @ 20°C: 0.7

Evaporation Rate (vs. ether = 1): 2.8

Flash Point (Closed Cup): < 0°C

Plastics Compatibility: to be checked (\*)

Non-Volatiles: None

Packaging: 500ml & 5L

---

## ■ APPLICATION INSTRUCTIONS

- Spray liberally and allow excess to run off. Air dry or dry with absorbent cloth. Repeat if necessary
- After application, re-lubricate with 40+ if necessary
- Check plastics and rubber compatibility before use. Do not use on sensitive electronics, use Ambertron for these applications
- Use with adequate ventilation. Do not use on energized equipment. Allow to dry thoroughly and vent before reactivating system

---

## ■ STORAGE AND SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50C, away from direct heat and naked flame.

---

## WARNING

Although the technical details and recommendations contained in this product data sheet are based on the best of our knowledge and experience, all the above information must be considered as indicative only.

Users must ensure, through prior testing, that MT-66 is suitable for the intended application and site conditions. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

## LEGAL NOTICE

- The contents of this Technical Data Sheet (TDS) may be copied into another project-related document; however, the resulting document shall not supplement or replace the requirements of the TDS in force at the time of application.
  - The most up-to-date TDS can be requested from Masters Touch Global Inc. or downloaded from the official website.
  - Any alteration to the wording, specifications, or requirements contained or derived from this TDS releases the manufacturer from any responsibility.
- 



For more information visit  
[masterstouchglobal.com](http://masterstouchglobal.com)