

PX-1

CUTTING COMPOUND

EXTERIOR
BODY-FIRST STEP

DESCRIPTION

A high-performance, easy-to-use rubbing compound designed to remove deep and minor scratches, imperfections, and oxidation from automotive paint surfaces.

KEY FEATURES

- Fast-cutting formula: Quickly removes deep and minor scratches and imperfections.
- Easy to use: Simple application and buffing process.
- High-gloss finish: Leaves a smooth, high-gloss finish.
- Safe for all paint finishes: Can be used on clear coat, single stage, and ceramic-coated paint surfaces.

TECHNICAL SPECIFICATIONS

- Appearance: White paste
- Viscosity: 20,000-30,000 cps
- PH: 8-10
- Solids content: 25-30%
- VOC (Volatile Organic Compound): 200-250 g/l

■ PHYSICAL PROPERTIES

- Density: 1.5-1.7 g/cm³
 - Flash point: >200°F (93°C)
 - Freezing point: <32°F (0°C)
-

■ PERFORMANCE CHARACTERISTICS

- Cutting power: 8-10 (on a scale of 1-10)
 - Gloss retention: 90-95% (after 24 hours)
 - Adhesion: Excellent adhesion to paint surfaces
-

■ APPLICATION INSTRUCTIONS

- Apply a small amount of rubbing compound to a clean wool or foam cutting pad.
 - Setup the buffing machine speed at 1000-1200 Rpm start with straight motion.
 - Buff the area with a clean, soft cloth to achieve a high-gloss finish.
 - Repeat #2 if necessary
-

■ PRECAUTIONS

- Avoid using in direct sunlight or high temperatures.
- Wear protective gloves and eyewear.
- Use in well-ventilated areas.

■ STORAGE AND SHELF LIFE

- Store in a cool, dry place.
 - Shelf life: 2 years from date of manufacture.
-

WARNING

Although the technical details and recommendations contained in this product data sheet are based on the best of our knowledge and experience, all the above information must be considered as indicative only.

Users must ensure, through prior testing, that MT-10 is suitable for the intended application and site conditions.

In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

■ LEGAL NOTICE

- The contents of this Technical Data Sheet (TDS) may be copied into another project-related document; however, the resulting document shall not supplement or replace the requirements of the TDS in force at the time of application.
 - The most up-to-date TDS can be requested from Masters Touch Global Inc. or downloaded from the official website.
 - Any alteration to the wording, specifications, or requirements contained or derived from this TDS releases the manufacturer from any responsibility.
-



For more information visit
[masterstouchglobal.com](https://www.masterstouchglobal.com)